



PATENT-PENDING FILL SYSTEM INCREASES PRODUCTIVITY UP TO 82%





Don't let tank refilling slow down your sprayer. The Spray Fill Xpress can **increase spraying productivity by as much as 82 percent**, thanks to its uniquely designed chemical batching process. This greatly speeds up filling time, reducing a 30-minute chore to **less than 7 minutes**. That means more time spent spraying and less time refilling. It's safe. It's easy. It's Field Tested Tough!

# **FEATURES & BENEFITS**

### **3-Inch Plumbing**

The extra large plumbing greatly reduces fill times. The system is fully flushable to help eliminate carry-over issues.

#### **Chemical Batching**

SFX 2430

The high capacity original model is 102 inches long (130 inches with pump) and can be fitted

with 3, 4, 5 or 6 tanks for a total of 240 gallons.

To save time, chemicals in the stainless steel tank can be portioned into individual containment areas where they will remain separate until drawn into the sprayer. This avoids premixing, which can cause undesirable reactions. Available flow meters and scales provide precise measurements.



Stainless steel tanks hold up to six different chemicals that can be added to the mix. Each tank includes a jug rinse system for convenient cleanout of chemical jugs.

#### **Deep Sump Tank**

The stainless steel chemical tanks have a deep, aggressively angled bottom that not only helps prevent splashing, but is integral in moving chemicals quickly into the sprayer. This design also allows complete drainage of the tanks, resulting in minimal cleanup.



SFX 1630

This smaller model can hold 2, 3 or 4 tanks for a total of 160 gallons, and at just 78 inches long (106 inches with pump) it will fit crossways on a trailer or easily inside an enclosed trailer.

#### **Rinse Wand**

The attached rinse wand provides a handy solution for cleaning the chemical tanks, and is ideal for making a slurry during dry chemical induction.

#### **Modular Design**

The Spray Fill Xpress has a modular design, letting you customize the unit with the number of stations and capacities you need.

#### **Optional Remote**

An optional remote control allows you to start and stop the water pump (optional), as well as adjust RPMs.

	SERIES	SFX2430	SFX1630	
Depth		36"	36"	
Length (wit	nout pump)	102"	78"	
Length (wit	n pump)	130"	106"	
Height (lid o	closed)	46"	46"	
Height (lid o	open)	78"	78"	



## Get More Spray Out of Every Day

#### 120-Foot Boom Width - 1,200 Gallon Tank - 12 Hour Day - Connect to Disconnect Time: 7:10 - Pump Start to Stop: 6:38

		Calculated Fill and Spray Total Time in Hours		Number of Fill and Spray Cycles Per Day		Acres Per Day			
Gallons Per Acre	Ground Speed (mph)	Conventional*	Spray Fill Xpress	Conventional*	Spray Fill Xpress	Conventional*	Spray Fill Xpress	Increased Coverage Per Day (Acres)	% Increase in Productivity
10	10	1.33	0.95	9	13	1,087	1,524	437	<b>40</b> %
10	12	1.19	0.81	10	15	1,213	1,783	570	<b>47</b> %
10	16	1.02	0.64	12	19	1,418	2,265	847	60%
15	10	1.05	0.67	11	18	914	1,433	519	<b>57</b> %
15	12	0.96	0.58	13	21	1,002	1,660	658	66%
15	16	0.84	0.46	14	26	1,138	2,070	932	<b>82</b> %

\*Based on 30-minute fill time.

